

Datasheet

System Configuration		C190-J	C190-N
Intel® Processor		Intel Bay Trail Quad Core Celeron J1900, 2GHz up to 2.42GHz, 2M Cache	Intel Bay Trail dual core Celeron N2807 CPU, Up to 2.16G, 1M Cache
Memory		DDR3L 1333MHz SO-DIMM x 1, Default 2G, max. 8GB	DDR3L 1333MHz SO-DIMM x 1, Default 2G, max. 4GB
Storage		SATA 2.5" hard drives (HDD) or flash storage (SSD)	
Power Supply		DC12V/5A external power adapter. AC100 to 240V full range.	
O/S Compatibility		Window 7, POS Ready7, Window 8.1, Industry Pro Retail 8.1, Linux	
"Physical Dimensions (W*H*D)"		Width: 372mm / Height: 310mm (full extended); 280mm (low-profile); 127mm (folded-flat) / Stand depth: 250mm	
System Weight(with stand)		8.2Kg / 3.8Kg(without stand)	8.4Kg / 4.0Kg(without stand)
Wall Mount		VESA 100X100mm compliant	
Product Certification		CE / FCC / BSMI	
Operation Temperature		0°C to 40°C	
Storage Temperature		-25°C to 70°C/td> , Humidity 15% ~ 80%	

LCD & Touch Panel		
Display	15" LED-backlight display	
Resolution	1024 x 768 (default) , Brightness 250 cd/m²	
Touch	Flat Type , Projected Capacitive Touch(PCAT) , USB Interface	Bezel Type , 5 wire Resistive Touch , USB Interface

I/O Connectivity	
Parallel	1 port DB-25 Printer Port (Standard)
USB	5 port , 4 x USB 2.0 +(1 x USB 2.0 or 1 x USB 3.0(option)
LAN	1 port RJ-45 LAN with activity and link LEDs 10/100/1000 Gb Ethernet
Serial	4 x DB-9, COM1 & COM3 Support 5V / 12V By Jumper
Cash Drawer	1 port RJ11 / Supports 2 Cash Drawer(12V)
Audio	HD Audio, 3W Speaker,1 x Line out,1 x Mic in
VGA	1 port DB-15
DC12V out Jack	1 port DC+12v/1A for P2+ Monitor
PS/2	1 port PS/2 KB
Extension Slot	mini-PCI-e slot x 1

Option	
2nd Display	9.7" LCD Panel , 1024 x 768 , VGA Port
MSR	MR100 : 2 or 3 Tracks , USB Interface
Customer Display	Back Mount , VFD 20x2, USB Interface
WiFi	WiFi 802.11 b/g/n.
SSD HDD	SATA 2.5" ,Minimum 64GB
RAID Card	RAID 1 Mode, 2nd HDD or SSD
USB 3.0	1 port
Wall Mount	VESA 100 x 100mm

product specifications subject to change without prior notice.

Certifications

FCC

CE

RoHS



12F-6,No.5,Sec.3,New Taipei Blvd, Sinhuang Dist, New Taipei City 24250, Taiwan(R.O.C)
TEL:+886-2-8521-5980 ,8522-5608 Email : sales@p2-plus.com
FAX:+886-2-8522-5861 WWW.p2-plus.com



Simply Better
POS!

Stylish and versatile design

