

# FLYTECH

POS

Build Smart Solutions for Tomorrow

## POS335



Fanless



WiFi



MSR



Fingerprint



2nd Display



Customer Display

### Application Benefits :


- Enhanced User/Customer Experience
- Ergonomic, Stylish and Compact
- Easy Serviceability and Upgradability



The POS 335 offers an outstanding combination of low-power consumption and high-efficient reliability for a smart compact POS system. The space-saving and easy-to-service characteristics make this small footprint POS terminal a perfect solution for the retail and hospitality industries. The POS 335 offers a seamless integration for a variety of peripheral modules such as MSR, Fingerprint, Second Display and Customer Display.

## Features

- 15" Resistive Touch
- Intel Bay Trail Processor
- Fanless and Silent
- Easy Swap HDD
- 3-Track MSR Available
- Fingerprint Available
- 2nd Display and Customer Display Available



## Specification

<b>Motherboard</b>	Type	D36
	Processor	Intel Bay Trail CPU Celeron J1900 2.4GHz
	Chipset	CPU Integrated
	System Memory	1x DDR3L SO-DIMM up to 8GB, 1066/1333MHz
	Graphic Engine	Intel HD graphic DX11
<b>LCD Touch Panel</b>	LCD Size	15" TFT LCD
	Brightness	250 nits
	Resolution	1024 x 768
	Touch Screen	Resistive Touch
	Tilt Adjustment	4° ~ 84°
<b>Storage Device</b>	Hard Drive	1x 2.5" SATA HDD
	Flash Memory	SATA SSD (Option)
<b>Expansion</b>	Mini PCI-E Socket	1
<b>External I/O Ports</b>	USB	1x USB3.0/2.0, 6x USB2.0
	Serial Port	3x RJ45 (powered RS232) (COM1/2 default 5V, COM3 default 12V)
	LAN	1x RJ45
	Cash Drawer	1x RJ11
	Parallel Port	1 (Option) (either 1x Parallel + 4x USB2.0 or 6x USB2.0)
	VGA	1x DB15
	Printer LED Indicator	1
	DC Jack	1
<b>Audio</b>	Internal Speaker	2x 2W
<b>Indicator</b>	LED Indicator	1
<b>Power</b>	Power Adapter	65W / 19V
<b>Communication</b>	Wireless LAN	802.11 b/g/n WLAN card & antenna (Option)
<b>Peripheral (Option)</b>	MSR	3-Track MSR (USB)
	Fingerprint	Fingerprint Reader (USB)
	2nd Display	8.4" without touch
	Customer Display	VFD display 2 x 20 characters (COM)
<b>Certificate</b>	EMC & Safety	FCC Class A, CE Mark, LVD
<b>Environment</b>	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing
<b>Dimension (WxDxH)</b>		365 x 216 x 343 mm (14.4" x 8.5" x 13.5")
<b>Weight</b>		5.8 kg (12.8 lbs)
<b>Mounting</b>		VESA Mount 100 x 100
<b>OS Supported</b>		Windows 7, POSReady 7, Windows Embedded 8.1 Industry, Windows 10 IoT Enterprise, Linux

### Taiwan - Headquarters

No.168, Sing-ai Rd., Neihs District,  
Taipei City 11494, Taiwan, R.O.C.  
Tel: 886-2-8791-4988  
Fax: 886-2-8791-4966  
E-mail: sales@flytech.com.tw  
www.flytech.com

### U.S.A. - California

728 Charcot Ave, San Jose,  
CA 95131, U.S.A  
Tel: 1-510-257-5180  
Fax: 1-510-257-5181  
E-mail: sales@flytech.com

### China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,  
Shanghai 200233, P.R.China  
Tel: 86-21-5426-1555  
Fax: 86-21-5426-1001  
E-mail: sales@flytech.com.cn  
www.flytech.com.cn

### China - Hong Kong

Room 01, 6/F, Block A, Tonic Industrial  
Centre, 26 Kai Cheung Road, Kowloon  
Bay, Kowloon, Hong Kong.  
Tel: 852-3525-5800  
Fax: 852-2751-7447  
E-mail: sales@flytech.com.hk